

TWO-STAGE SNOWBLOWERS

POWER MAX®



724 OE
37770

726 OE
37771

826 OE
37772

POWER MAX® HD



928 OE
38660

926 OXE
38664

1028 OXE
38674

1128 OXE
38680

| PERFORMANCE | | | | | | | |
|-------------------------------------|-------------------------------------|-------------------------------------|---------------------------------------|--|--|--|--|
| Capacity / Minute* | Up to 1800 lbs. (818 kg) | ▶ Up to 1900 lbs. (864 kg) | Up to 1900 lbs. (864 kg) | ▶ Up to 2000 lbs. (909 kg) | Up to 1900 lbs. (864 kg) | ▶ Up to 2100 lbs. (955 kg) | ▶ Up to 2200 lbs. (1000 kg) |
| Throw Distance* | Up to 40' (12 m) | Up to 40' (12 m) | Up to 40' (12 m) | ▶ Up to 45' (13.5 m) | Up to 45' (13.5 m) | Up to 45' (13.5 m) | Up to 45' (13.5 m) |
| Clearing Width | 24" | ▶ 26" | 26" | ▶ 28" | 26" | ▶ 28" | 28" |
| Power Steering | N/A | N/A | N/A | N/A | ▶ Standard | Standard | Standard |
| Speeds | 6 Forward 2 Reverse | 6 Forward 2 Reverse | 6 Forward 2 Reverse | 6 Forward 2 Reverse | 6 Forward 2 Reverse | 6 Forward 2 Reverse | 6 Forward 2 Reverse |
| Snow Cut Depth – 1 Pass | 20" | 20" | 20" | ▶ 21.5" | 21.5" | 21.5" | 21.5" |
| Auger System | Anti-Clogging System (ACS) | Anti-Clogging System (ACS) | Anti-Clogging System (ACS) | Anti-Clogging System (ACS) | Anti-Clogging System (ACS) | Anti-Clogging System (ACS) | Anti-Clogging System (ACS) |
| Auger Diameter | 11" | 11" | 11" | ▶ 14" | 14" | 14" | 14" |
| Auger Gearbox | Hardened Gears | Hardened Gears | Hardened Gears | ▶ Commercial-Grade; no shear pins needed | Commercial-Grade; no shear pins needed | Commercial-Grade; no shear pins needed | Commercial-Grade; no shear pins needed |
| MOTOR | | | | | | | |
| Engine | 205cc Briggs & Stratton OHV 4-cycle | 205cc Briggs & Stratton OHV 4-cycle | ▶ 250cc Briggs & Stratton OHV 4-cycle | ▶ 265cc Toro Premium OHV 4-cycle | 265cc Toro Premium OHV 4-cycle | ▶ 302cc Toro Premium OHV 4-cycle | ▶ 342cc Briggs & Stratton OHV 4-cycle |
| Starter | Electric Start | Electric Start | Electric Start | Electric Start | Electric Start | Electric Start | Electric Start |
| Fuel Capacity | 3.2 Quarts (3 L) | 3.2 Quarts (3 L) | 3.2 Quarts (3 L) | 3.4 Quarts (3.2 L) | 3.4 Quarts (3.2 L) | 3.4 Quarts (3.2 L) | 3.2 Quarts (3 L) |
| USER-FRIENDLY FEATURES | | | | | | | |
| Chute Control | Quick Lever | ▶ Quick Stick® | Quick Stick | Quick Stick | Quick Stick | Quick Stick | Quick Stick |
| Skids | Standard | Standard | Standard | Standard | ▶ Heavy Duty | Heavy Duty | Heavy Duty |
| One-Hand Interlock | Yes | Yes | Yes | Yes | Yes | Yes | Yes |
| Scraper | Adjustable | Adjustable | Adjustable | Adjustable | Adjustable | Adjustable | ▶ Pivoting |
| Tires | 13" | 13" | 13" | ▶ 15" | ▶ 16" | 16" | 16" |
| Headlight | N/A | N/A | N/A | ▶ Yes | Yes | Yes | Yes |
| Weight | 171 lbs. (78 kg) | 173 lbs. (78 kg) | 175 lbs. (79 kg) | 243 lbs. (110 kg) | 262 lbs. (119 kg) | 267 lbs. (121 kg) | 269 lbs. (122 kg) |
| Machine Warranty** | 3-Year Limited | 3-Year Limited | 3-Year Limited | 3-Year Limited | 3-Year Limited | 3-Year Limited | 3-Year Limited |
| Deflector, Bypass, Chute Warranty** | Guaranteed for Life | Guaranteed for Life | Guaranteed for Life | Guaranteed for Life | Guaranteed for Life | Guaranteed for Life | Guaranteed for Life |

We reserve the right to improve our products and make changes in the specifications, designs and standard equipment without notice and without incurring obligation. Products depicted in this brochure are for demonstration purposes only. Actual products offered for sale may vary in design, required attachments and safety features.

▶ Enhanced or step-up feature.

* Capacity and throw distance will vary with conditions.

** See retailer for full warranty details or go to toro.com (U.S.) or toro.ca (Canada). Specifications, design and accessories are subject to change without notice.

TWO-STAGE SNOWBLOWER ACCESSORIES

See your dealer for additional information on our snowblower accessories.



SKID SHOES



SNOW CAB



COVER



DRIFT BREAKER